

Bodro 10W-40

The excellent wear performance technology ensures the engines optimal performance, by extending oil change intervals, maintaining wear protection and fuel conservation. Suitable for gasoline and diesel engines, with and without exhaust gas turbocharging.



Properties

- + Excellent low temperature performance
- + Excellent fuel economy performance
- + Cold start properties
- + Excellent wear performance technology

Specifications

API SN/CF
 ACEA A3/B4
 VW 502 00/505 00
 MB 229.5
 Renault RN 0700/0710

Table of properties

Property	Test Method	Unit	Value
Density 15°C	ASTM D 4052	g/ml	0.860
Kinematic Viscosity @ 40°C	ASTM D 445	cSt	101.67
Kinematic Viscosity @ 100°C	ASTM D 445	cSt	15.42
Viscosity Index	ASTM 2270	None	160.54
Viscosity at -25°C (CCS)	ASTM D 5293	mPas	≤ 7000
Total Acid Number TBN	ASTM 2896	mg KOH/g	6.8
Pour Point °C	ASTM D 97	°C	-36
Flash Point °C	ASTM D 92	°C	226

* Characteristic values can fluctuate within the normal range. The information in this publication is based on our current knowledge and experience. They do not release the user from their own tests and trials due to possible influences during the processing and application of our products. A legally binding assurance of certain properties or the suitability for a specific application cannot be derived from our information. It is the responsibility of the recipient of our products to observe any property rights as well as existing laws and regulations.

