

Bodro 15W-40

This semi-synthetic engine oil suitable for aspirated and turbo charged diesel and gasoline engine oils. The innovative formula and premium quality base oils used in the production of Bodro 15W-40 prevent sludge build up and deposits from damaging the engine and thus increase engine life.



Properties

- + Excellent fuel economy performance
- + Excellent wear performance technology
- + Sludge build up prevention
- + Very high resistance against Oxidation

Specifications

API SN/CF
 VW 502 00 /503 00/505 00
 ACEA A3/B3
 MB 229.1
 Renault RN 0700/0710
 PSA B 71 2300

Table of properties

Property	Test Method	Unit	Value
Density 15°C	ASTM D 4052	Kg/m ³	865.8
Kinematic Viscosity @ 40°C	ASTM D 445	cSt	106.00
Kinematic Viscosity @ 100°C	ASTM D 445	cSt	14.27
Viscosity Index	ASTM D 2270		137
Pour Point °C	ASTM D 97		-45
Flash Point °C	ASTM D 97		241

* Characteristic values can fluctuate within the normal range. The information in this publication is based on our current knowledge and experience. They do not release the user from their own tests and trials due to possible influences during the processing and application of our products. A legally binding assurance of certain properties or the suitability for a specific application cannot be derived from our information. It is the responsibility of the recipient of our products to observe any property rights as well as existing laws and regulations.

