

Germany

LUBPLUS GmbH | Radlkoferstr. 2 | 81373 München | Germany

CAT Clean

Lubplus CAT Clean cleans the entire fuel system thanks to the latest additive technology. It dissolves resinification in the fuel system as well as gummed carbon deposits on lambda probes and catalytic converters. Suitable and recommended for use in all petrol and diesel engines.



Properties

- + Prevents heavy contamination, if it is used regularly.
- + Optimizes fuel efficiency.
- + Optimizes engine performance.
- + Supports the proper function of the catalytic converter and oxygen sensor.
- Can help to avoid expensive workshop visits or breakdowns.

Application

- + Add with every tank filling to the tank before filling up.
- + Works during operation.
- → Sufficient for up to 60 80 L of fuel. For larger tank volumes add 50 ml per 10 L of the filling content.

Table of properties

Property	Test Method	Unit	Value
Density	DIN 12185	g/cm ³	0.88
Kinematic Viscosity @ 40°C Flash Point °C	ISO 3679	mPa·s ºC	< 7 > 61
Color/Appearance		Colourles	s liquid

^{*} Characteristic values can fluctuate within the normal range. The information in this publication is based on our current knowledge and experience. They do not release the user from their own tests and trials due to possible influences during the processing and application of our products. A legally binding assurance of certain properties or the suitability for a specific application cannot be derived from our information. It is the responsibility of the recipient of our products to observe any property rights as well as existing laws and regulations.