

# Galopper 15W-40

Galopper 15W-40 is a mineral oil suitable for aspirated and turbo charged diesel and gasoline engine oils. The innovative formula protects the engine from the day to day driving conditions whilst extending the engine life.



## Properties

- + Sludge build up prevention
- + Excellent wear performance technology
- + Excellent fuel economy performance
- + Very high resistance against Oxidation

## Specifications

API SL/CF  
 VW 505 00  
 ACEA A3/B2  
 MB 229.1

## Table of properties

Property	Test Method	Unit	Value
Density 15°C	ASTM D 4052	Kg/m <sup>3</sup>	865.8
Kinematic Viscosity @ 40°C	ASTM D 445	cSt	106.00
Kinematic Viscosity @ 100°C	ASTM D 445	cSt	14.27
Viscosity Index	ASTM D 2270		137
MRV at -25°C	ASTM D 4684	cP	17000
Pour Point °C	ASTM D 97		-45
Flash Point °C	ASTM D 97		241

\* Characteristic values can fluctuate within the normal range. The information in this publication is based on our current knowledge and experience. They do not release the user from their own tests and trials due to possible influences during the processing and application of our products. A legally binding assurance of certain properties or the suitability for a specific application cannot be derived from our information. It is the responsibility of the recipient of our products to observe any property rights as well as existing laws and regulations.

