

Galopper_{FG} 20W-50

Galopper FG 20W-50 is a high-quality mineral oil for older gasoline and diesel engines of vehicles with or without turbo compressors. The combination of selected additive packages and a high-performance base oil ensures excellent resistance against foaming, corrosion and wear while increasing engine life.



Properties

- + Protection to wear and tear
- + Excellent resistance against foaming, corrosion and oxidation
- + High dispersion and detergency level
- + Stable viscosity index

Specifications

API SF/CD

Table of properties

Property	Test Method	Unit	Value
Density 15°C	ASTM D 4052	Kg/L	0.882
Kinematic Viscosity @ 40°C	ASTM D 445	cSt	167
Kinematic Viscosity @ 100°C	ASTM D 445	cSt	18.7
Viscosity Index	ASTM D 2270		127
TBN	ASTM D 2896	mg KOH/g	7
Sulfated Ash	ASTM D 874	wt%	0.9
Pour Point °C	ASTM D 97		-24
Flash Point °C	ASTM D 92		244

* Characteristic values can fluctuate within the normal range. The information in this publication is based on our current knowledge and experience. They do not release the user from their own tests and trials due to possible influences during the processing and application of our products. A legally binding assurance of certain properties or the suitability for a specific application cannot be derived from our information. It is the responsibility of the recipient of our products to observe any property rights as well as existing laws and regulations.

